



Hazardous duty window air conditioners

This unit is designed to operate in Class I, Group C & D, Division 1 hazardous environments. It fits standard windows or equivalent through the wall applications. Installation is limited to single opening and a single feed in power source. All operating controls are self-contained.

FEATURES

- ☐ Mounts within two inches flush with interior wall
- ☐ Aluminum or plastic blowers and fans
- ☐ All sparking devices in explosion proof enclosures
- ☐ Four way adjustable air distribution
- ☐ Washable air filter
- ☐ Slide out chassis
- ☐ Static free belts
- ☐ Aluminum pulleys
- ☐ Phenolic coatings for hostile operating environments
- ☐ Available as Class I, Group C & D, Division 2 environment

OPTIONS

SPECIFICATIONS

MODEL	COOLING CAPACITY * (BTU)	VOLTAGE	AMPS	WIDTH (IN)	DEPTH (IN)	HEIGHT (IN)	WEIGHT (LBS)
XRAC-012-3	11400	115-1-60	12.4	26	28	29-1/2	253
XRAC-018-3	17500 / 17200	230/208-1-60	8.6 / 9.1	26	28	29-1/2	295
XRAC-024-3	24900 / 24600	230/208-1-60	13.9 / 15.4	28-1/4	34	33-1/2	335
XRAC-030-3	27900 / 27400	230/208-1-60	14.6 / 16.1	28-1/4	34	33-1/2	346
XRAC-035-3	35000 / 34800	230/208-1-60	18.0 / 20.0	28-1/4	34	33-1/2	381

* Capacities based on 95° F ambient and 80° FDB / 69° FWB entering air conditions

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

